
**HK6020**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK, single row, with cageMateriálové číslo Schaeffler:
0002732360000

Technické informace



Vaše aktuální varianta produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	60 mm	Under roller diameter
D	68 mm	Outside diameter
C	20 mm	Width
C_r	33.500 N	Basic dynamic load rating, radial
C_{0r}	75.000 N	Basic static load rating, radial
C_{ur}	9.900 N	Fatigue load limit, radial
n_G	4.450 1/min	Limiting speed
$n_{G\text{ Grease}}$	2.650 1/min	Limiting speed for grease lubrication
n_{gr}	3.500 1/min	Reference speed
$\approx m$	81,364 g	Hmotnost

Dimensions

C_1	20 mm	Width, outer ring
$r_{\min}$	0,8 mm	Minimum chamfer dimension



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	140 °C	Operating temperature max.

Vlastnosti



Radiální zatížení



Mazání (plastickým) mazivem



Mazání olejem



Neutěsněné



Malý konstrukční prostor