
**HK6032**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK, single row, with cageMateriálové číslo Schaeffler:
0002826500000

Technické informace



Vaše aktuální varianta produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	60 mm	Under roller diameter
D	68 mm	Outside diameter
C	32 mm	Width
C_r	53.000 N	Basic dynamic load rating, radial
C_{0r}	135.000 N	Basic static load rating, radial
C_{ur}	20.000 N	Fatigue load limit, radial
n_G	4.450 1/min	Limiting speed
$n_{G_{Grease}}$	2.650 1/min	Limiting speed for grease lubrication
n_{gr}	3.400 1/min	Reference speed
$\approx m$	131,178 g	Hmotnost

Dimensions

C_1	32 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	140 °C	Operating temperature max.

Vlastnosti



Radiální zatížení



Mazání (plastickým) mazivem



Mazání olejem



Neutěsněné



Malý konstrukční prostor