

**KGB040-PP-AS** **Linear Ball Bearing and Housing Unit**

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Materiálové číslo Schaeffler:
0015663930000

Technické informace**n.r.**

	PP	Seal
	AS	Relubrication facility
≈m	1,28 kg	Hmotnost

Main Dimensions & Performance Data

H	79,5 mm	Center height
L	80 mm	Length
Tol L	h12	Tolerance
B	108 mm	Width
C	6.100 N	Load capacity dyn.
C ₀	4.600 N	Load capacity stat. C ₀

**Mounting dimensions**

J _B	94 mm	
Tol J _B	+0,2	Upper tolerance
Tol J _B	-0,2	Lower tolerance
B ₁	77 mm	
A ₅	54 mm	
Tol A ₅	+0,02	Upper tolerance
Tol A ₅	-0,02	Lower tolerance
B ₂	18,2 mm	
L ₄	40 mm	Distance
L ₅	56 mm	Distance
J L ₄	23 mm	Distance
H ₂	45 mm	Height shaft
Tol H ₂	+0,015	Upper tolerance
Tol H ₂	-0,015	Lower tolerance
A ₃	30 mm	
H ₆	12 mm	
N ₁	9 mm	
N ₃	15 mm	
K ₅	M8	
K ₈	NIPA2	Lubrication nipple
α	54 °	Angle
	5	Ball rows