

FAG



23034-E1A-XL-K-M

Spherical Roller Bearing

Spherical roller bearings 230...E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Technické informace



Vaše aktuální varianta produktu

Design	E1A	without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	
Special material	Standard	

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	260 mm	Outside diameter
B	67 mm	Width
C _r	880.000 N	Basic dynamic load rating, radial
C _{0r}	1.230.000 N	Basic static load rating, radial
C _{ur}	151.000 N	Fatigue load limit, radial
n _G	2.800 1/min	Limiting speed
n _{gr}	1.890 1/min	Reference speed

≈m	12,024 kg	Hmotnost
----	-----------	----------



Mounting dimensions

d _{a min}	180,2 mm	Minimum diameter shaft shoulder
D _{a max}	249,8 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius
d _{a max}	190 mm	Maximum diameter of shaft shoulder
d _{b min}	179 mm	Minimum cavity diameter of the sleeve
B _{a min}	8 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
D ₁	237,2 mm	Bore diameter outer ring
d _s	6,3 mm	Diameter lubrication hole
n _s	12,2 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,98	Dynamic axial load factor
Y ₂	4,44	Dynamic axial load factor
Y ₀	2,92	Static axial load factor

Additional information

H3034	Adapter sleeve
AH3034	Withdrawal sleeve



Vlastnosti



Radiální zatížení



Axiální zatížení v jednom směru



Axiální zatížení ve dvou směrech



Mazání (plastickým) mazivem



Mazání olejem



Neutěsněné



Statická úhlová chyba a vychýlení



Dynamická úhlová chyba a vychýlení