



Brand of NTN corporation

Technical data

UCF211N

Bearing units




Grey cast housing, radial insert ball bearing with socket set screws, seal with slinger

KIT CONTENT

UC211G2, F211N

VISUAL (S)



PRODUCT DEFINITION

Brand	SNR
A - Housing height	43 mm
A1 - Housing foot height / flange height	18 mm
A2 - Total height from mounting surface	58,4 mm
B - Width of Inner Ring	55,6 mm
d - Shaft diameter	55 mm



NTN Europe

1 rue des Usines · BP 2017 · 74010 Annecy Cedex · France · Tel. +33 (0)4 50 65 30 00
S.A. au capital de 322 639 919 € · RCS ANNECY B 325 821 072 · Id. Fiscale : FR 48 325 821 072
SIRET 325 821 072 00015 · Code APE 2815 Z · Code NACE 28.15

PRODUCT DEFINITION

e - Distance mounting surface to bearing center	25 mm
G - Grease fitting	M6x1
J - Mounting holes distance	130 mm
L - Housing width / diameter	162 mm
N - Mounting hole dimension	19 mm
S - Distance front side/bearing centre	22,2 mm

PRODUCT PERFORMANCE

C - Dynamic load rating	43,55 kN
C0 - Static load rating	29,2 kN
Operating temperature min.	-20 °C
Operating temperature max.	100 °C

OTHER FEATURES

Mass	3,28 kg
Recommended tightening torque for set screw	22 N-m

KIT COMPONENT

Designation of housing	F211N
Designation of insert bearing	UC211G2

ESHOPDONOTDISPLAY

Reference	UCF211N
Selection cover [Yes / No]	Non/No
Datasheet Type	UCF200N
Tracepart	Non/No
Image	UCF200N_1.jpg, UCF200N_3.jpg



ESHOPDONOTDISPLAY

Dimension system	Métrique/Metric
Units Type	Flanged units
Material of Housing	Cast iron

