



Brand of NTN corporation

Technical data

USFD203M6

Bearing units




Grey cast housing, radial insert ball bearing with socket set screws, single lip seal

KIT CONTENT

US.203.G2, FD203G

VISUAL (S)



PRODUCT DEFINITION

Brand	SNR
A - Housing height	15 mm
A2 - Total height from mounting surface	24,4 mm
B - Width of Inner Ring	22 mm
d - Shaft diameter	17 mm
e - Distance mounting surface to bearing center	8,4 mm



NTN Europe

1 rue des Usines · BP 2017 · 74010 Annecy Cedex · France · Tel. +33 (0)4 50 65 30 00
S.A. au capital de 322 639 919 € · RCS ANNECY B 325 821 072 · Id. Fiscale : FR 48 325 821 072
SIRET 325 821 072 00015 · Code APE 2815 Z · Code NACE 28.15

PRODUCT DEFINITION

G - Grease fitting	M6x1
H - Housing length, width or diameter	81 mm
J - Mounting holes distance	63,5 mm
L - Housing width / diameter	58,7 mm
N1 - Mounting hole thread	M6
S - Distance front side/bearing centre	6 mm

PRODUCT PERFORMANCE

C - Dynamic load rating	9,55 kN
C0 - Static load rating	4,78 kN
Operating temperature min.	-20 °C
Operating temperature max.	100 °C

OTHER FEATURES

Mass	0,3 kg
Recommended tightening torque for set screw	3.5 N-m

