



K105X112X21

Needle roller cage assembly

Needle roller cage assembly K, single row

Technické informace



Vaše aktuální varianta produktu

Cage	JN	Steel sheet metal
------	----	-------------------

Main Dimensions & Performance Data

F _w	105 mm	Inner diameter of needle roller complement
----------------	--------	--

E _w	112 mm	Outside diameter of needle roller complement
----------------	--------	--

B _c	21 mm	Width
----------------	-------	-------

C _r	47.500 N	Basic dynamic load rating, radial
----------------	----------	-----------------------------------

C _{0r}	127.000 N	Basic static load rating, radial
-----------------	-----------	----------------------------------

C _{ur}	17.700 N	Fatigue load limit, radial
-----------------	----------	----------------------------

n _G	4.500 1/min	Limiting speed
----------------	-------------	----------------

n _{gr}	3.000 1/min	Reference speed
-----------------	-------------	-----------------

m	0,132 kg	Hmotnost
---	----------	----------

Temperature range

T _{min}	-30 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	140 °C	Operating temperature max.
------------------	--------	----------------------------



Vlastnosti



Radiální zatížení



Mazání (plastickým mazivem)



Mazání olejem



Neutěsněné



Malý konstrukční prostor