



FAG

NUP2318-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-XL-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

Materiálové číslo Schaeffler: 0382621500000

X-life




Technické informace

Vaše aktuální varianta produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	190 mm	Outside diameter
B	64 mm	Width
C _r	510.000 N	Basic dynamic load rating, radial
C _{0r}	530.000 N	Basic static load rating, radial
C _{ur}	94.000 N	Fatigue load limit, radial
n _G	6.300 1/min	Limiting speed
n _{gr}	3.000 1/min	Reference speed
≈m	8,915 kg	Hmotnost





Mounting dimensions

d_1	124 mm	Maximum rib diameter inner ring
$D_{1 \min}$	161,62 mm	Minimum rib diameter outer ring
$d_{a \min}$	104 mm	Minimum diameter shaft shoulder
$d_{c \min}$	127 mm	Minimum shaft shoulder
$D_{a \max}$	176 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$r_{1 \min}$	3 mm	Minimum chamfer dimension
E	169,5 mm	Raceway diameter outer ring
F	113,5 mm	Raceway diameter inner ring
B_3	10 mm	Width of loose rib

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Vlastnosti



Radiální zatížení



Axiální zatížení v jednom směru



Axiální zatížení ve dvou směrech



Mazání (plastickým mazivem)



Mazání olejem



Neutěsněné