


**FAG****NUP232-E-XL-M1**

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-XL-M1,
with cage, single row, locating bearing, 2 ribs
on outer ring, 1 rib on inner ring, rib washer
internal, type NUP

X-life

Technické informace



Vaše aktuální varianta produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	48 mm	Width
C _r	590.000 N	Basic dynamic load rating, radial
C _{0r}	670.000 N	Basic static load rating, radial
C _{ur}	102.000 N	Fatigue load limit, radial
n _G	4.200 1/min	Limiting speed
n _{gr}	2.160 1/min	Reference speed
≈m	14,86 kg	Hmotnost



Mounting dimensions

d ₁	206,8 mm	Maximum rib diameter inner ring
D _{1 min}	249,6 mm	Minimum rib diameter outer ring
d _{a min}	174 mm	Minimum diameter shaft shoulder
d _{c min}	210 mm	Minimum shaft shoulder
D _{a max}	276 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
r _{1 min}	3 mm	Minimum chamfer dimension
E	259 mm	Raceway diameter outer ring
F	195 mm	Raceway diameter inner ring
B ₃	8 mm	Width of loose rib

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Vlastnosti

- Radiální zatížení
- Axiální zatížení v jednom směru
- Axiální zatížení ve dvou směrech
- Mazání (plastickým mazivem)
- Mazání olejem
- Neutěsněné